

Enforcing Sets of Formulas in Structured Argumentation

AnneMarie Borg¹ and Floris Bex^{1,2}

¹Department of Information and Computing Sciences, Utrecht University

²Tilburg Institute for Law, Technology, and Society, Tilburg University

Abstract

Enforcement, adjusting an argumentation framework such that a certain set of arguments becomes acceptable, is an important research topic within the study of dynamic argumentation, but one that has been little studied for structured argumentation. In this paper we study enforcement in a general structured argumentation setting. In particular, we study conditions on the argumentation setting and the knowledge base that ensure (or prevent) the acceptability of sets of formulas for structured argumentation frameworks.

1 Introduction

Argumentation is a dynamic process, in which derived conclusions have to be revised in view of new information. However, basic abstract Argumentation Frameworks (AFs) – arguments and the attacks between them [27] – and their conclusions – set(s) of arguments (extensions) that can collectively be accepted – are static. Dynamic approaches to abstract argumentation have been studied, such as *enforcement* [8]: given a set of arguments that we want to accept, how to change the argumentation framework in such a way that this set becomes (part of) an extension in the resulting framework?

Although enforcement has been extensively studied for abstract argumentation (see [24] for an overview), not much research has been conducted on enforcement for structured argumentation, where arguments can be constructed by inferring conclusions (formulas) from a knowledge base (a set of formulas). In abstract argumentation, dynamics is often modeled by adding arguments/attacks, but in structured argumentation it is not possible to simply add specific arguments/attacks without directly influencing other arguments/attacks in the framework. The structure of individual arguments means that there is a sub-argument relation, for example, when an argument is based on a subset of the premises (formulas) of another argument. Thus, adding an argument means that its sub-arguments have to be added as well. Similarly, because attacks are dependent on the formulas in the arguments, adding an attack could mean that we have to add an argument as well. Hence, in a structured setting we should define enforcement *in terms of formulas* instead of in terms of arguments: given a set of formulas that you want to accept, how to change the framework in such a way that this set becomes (part of) the conclusions of an extension in the resulting framework?

For our study of enforcement of sets of formulas, we take a general approach to structured argumentation [15] so the results hold for many of the well-known approaches [11]. We allow formulas to be added to the knowledge base, and show under which conditions on the attack relation and on the new information in the knowledge base a set of formulas can be enforced. We see that a set of formulas can always be enforced if it can be derived from a consistent set of formulas and either (i) that set is maximally consistent; or (ii) the acceptance relation is monotonic; or (iii) the acceptance relation satisfies non-interference and the set does not share any information with the already existing information. To the best of our knowledge, this is the first study on enforcement of sets of formulas in a general structured argumentation setting.

Our study of enforcement in a structured argumentation setting is not only interesting from a theoretical perspective. There are many real-world applications of structured argumentation, including those in legal

The final version was published in the Proceedings of the 18th International Conference on Principles of Knowledge Representation and Reasoning (KR'21): <https://doi.org/10.24963/kr.2021/13>.

reasoning [40], crime and forensics [12, 37], medicine [21, 48], technologies for behaviour change [19] and debunking fake news [45]. In these application domains, dynamics and specifically enforcement for structured argumentation is imperative. For example, when reasoning in legal or medical cases we want to know whether new observations can enforce a new (legal/medical) conclusion or whether we can stop looking for more evidence. Similarly, in persuasive dialogues for behaviour change or about fake news, it makes sense to enforce one’s conclusion in as short a dialogue as possible, since in the case of long dialogues the user will simply disengage.

We start our paper by further illustrating the need for enforcement in a real-life application of structured argumentation (Section 2). The setting from [15] and enforcement for abstract argumentation [8] are recalled in Section 3. Then, in Section 4, enforcement in a structured setting are introduced. Finally, we discuss the implications of some of the assumptions and restrictions made in the paper in Section 5 and related work in Section 6. We conclude in Section 7.

2 Enforcement in Real-world Applications

At the Dutch National Police several argumentation-based applications are being deployed [12]. These applications are aimed at assisting the police at working through high volume tasks, leaving more time for tasks that require human attention. For example, there is an application that helps Dutch citizens to file a complaint on online trade fraud and can then determine whether it is a case of fraud [38], and an application helps the police to identify malafide webshops [37]. Each of these applications is based on an inquiry process in which the system gathers information until the argumentation component (which is based on a variation of ASPIC⁺ [39]) determines that the derived conclusion will not change if more information is added (i.e., the conclusion is *stable*).

Take, for example, the application for online trade fraud. This system tries to determine whether, given the information that the citizen has provided, the conclusion for *fraud* can be stably accepted (i.e., it is currently accepted and will remain so with any future expansion of the knowledge base), or not (e.g., no (accepted) argument for *fraud* is possible given the current knowledge base, or the acceptance of *fraud* might still change when new information is obtained). Essentially, the question is whether the conclusion *fraud* can be enforced for all possible expansions of the knowledge base, and if so, what information is necessary for this enforcement. The application contains a rule-base (based on Dutch fraud law) and a set of queryables, formulas that can be added to the knowledge base and from which (given the rule-base) it might be possible to build arguments for the conclusion *fraud*. These queryables are observations that can be gathered by, for example, asking the citizen more questions (e.g., ‘how much did you pay to the suspected fraudster?’) or querying a database (e.g., ‘is the suspected fraudster known to the police?’). The question of enforcement becomes then: which of these queryables should be added to the knowledge base to enforce the conclusion *fraud*? Since the application (and the other applications mentioned here and in Section 1) are based on structured argumentation frameworks (in the case of the trade fraud application a variation of ASPIC⁺), the existing literature on enforcement does not help to answer this question. In this paper we therefore study enforcement for structured argumentation in a general setting, the results of which are general enough to be implemented in the police applications as well.

3 Preliminaries

In this paper it is assumed that there is a formal language \mathcal{L} . Sets of formulas are denoted by S, T , finite sets of formulas are denoted by Γ, Δ, Θ , formulas are denoted by $\gamma, \delta, \phi, \psi$ and atoms are denoted by p, q, r , all of which can be primed or indexed if needed. Furthermore, it is assumed that there is a *deducability relation* $\vdash_{\subseteq} \wp_{\text{fin}}(\mathcal{L}) \times \mathcal{L}$ (where \wp_{fin} denotes the set of finite subsets).

For the results in this paper it is not necessary to assume all the Tarskian conditions on \vdash (i.e., reflexivity, transitivity and monotonicity). Given a language \mathcal{L} , a set of \mathcal{L} -formulas S and a deducability relation \vdash , we denote the closure of S w.r.t. \vdash by $\text{CN}_{\vdash}(S) = \{\phi \mid \exists \Gamma \subseteq S \text{ s.t. } \Gamma \vdash \phi\}$. When \vdash is clear from the context it will be omitted.

3.1 General Argumentation Setting

Abstract argumentation frameworks [27] are pairs $\mathbb{AF} = \langle \text{Args}, \mathbb{A} \rangle$, where Args is a set of arguments and $\mathbb{A} \subseteq \text{Args} \times \text{Args}$ is an attack relation on those arguments – in such frameworks, the arguments are abstract entities with no internal content or structure. In structured argumentation the arguments in an argumentation framework are constructed from a knowledge base and a set of rules and the attack relation is based on the structure of these arguments.

Rather than choosing one of the well-known approaches to structured argumentation (see e.g., [11]) as the framework for this paper, the general argumentation setting from [15] is taken as the argumentation approach. This allows us to keep the results of the current paper as general as possible and does not require to introduce all the specifics of one particular approach. Moreover, the results apply to some (e.g., ASPIC⁺, ABA and logic-based argumentation) of the approaches discussed in [11], since it was shown in [15] that these can be translated into the general setting. We recall here the most important definitions from [15].

Definition 1 (Argument). Given a set of \mathcal{L} -formulas S , the set of S -based arguments is denoted by $\text{Args}_{\perp}(S)$, such that $(\Gamma, \gamma) \in \text{Args}_{\perp}(S)$ iff $\Gamma \vdash \gamma$ for some $\Gamma \subseteq S$. Given an argument $a = (\Gamma, \gamma) \in \text{Args}_{\perp}(S)$, $\text{Conc}(a) = \gamma$ denotes the conclusion of a and $\text{Supp}(a) = \Gamma$ denotes the support set of a . Where S is a set of arguments, $\text{Supps}(S) = \bigcup \{\text{Supp}(a) \mid a \in S\}$ and $\text{Concs}(S) = \{\text{Conc}(a) \mid a \in S\}$.

To accommodate argumentative attacks two types of functions are introduced: a *contrariness function* $\bar{\cdot} : \mathcal{L} \rightarrow \wp(\mathcal{L})$ that associates each formula with a set of conflicting formulas and a *target function* $\hat{\cdot} : \wp_{\text{fin}}(\mathcal{L}) \setminus \emptyset \rightarrow \wp_{\text{fin}}(\mathcal{L})$ that associates the support set of each argument with the sets of formulas in which the argument can be attacked.

Example 1. Let \mathcal{L} be a formal language and \vdash_{CL} the consequence relation from classical logic (CL). Some examples of the contrariness and target function are:

$$\begin{aligned} \text{negation } (\neg): \bar{\phi} &= \{\neg\phi\} & \text{conflict}: \bar{\phi} &= \{\psi \mid \psi, \phi \vdash \perp\} \\ \text{identity } (\text{id}): \hat{\Gamma} &= \Gamma & \text{conjunction}: \hat{\Gamma} &= \{\bigwedge \Gamma' \mid \Gamma' \subseteq \Gamma\}. \end{aligned}$$

An argumentation setting is based on the deducability relation, the contrariness function and the target function.

Definition 2 (Setting). An (*argumentation*) *setting* is a triple $\mathbb{AS}_{\perp} = (\vdash, \bar{\cdot}, \hat{\cdot})$. A setting based on $S \subseteq \mathcal{L}$ is given by $\mathbb{AS}_{\perp}(S) = (S, \vdash, \bar{\cdot}, \hat{\cdot})$.

Attacks between arguments in a setting are based on the contrariness function and the target function:

Definition 3 (Attacks). Let $\mathbb{AS}_{\perp}(S)$ be a setting and let $a = (\Gamma, \gamma) \in \text{Args}_{\perp}(S)$ and $b = (\Delta, \delta) \in \text{Args}_{\perp}(S)$. Then a *attacks* b (in ϕ) iff there is a $\phi \in \hat{\Delta}$ such that $\gamma \in \bar{\phi}$.

Given a setting the corresponding argumentation framework can be defined.

Definition 4 (Argumentation framework). Given a setting $\mathbb{AS}_{\perp}(S)$, the corresponding *argumentation framework* is the pair $\mathbb{AF}(\mathbb{AS}_{\perp}(S)) = \langle \text{Args}_{\perp}(S), \mathbb{A} \rangle$, where $\text{Args}_{\perp}(S)$ is the set of S -based arguments and $(a, b) \in \mathbb{A}$ iff $a, b \in \text{Args}_{\perp}(S)$ and a attacks b .

Example 2. Let $\mathbb{AS}_{\text{CL}}(S) = (S, \vdash_{\text{CL}}, \neg, \text{id})$ be an argumentation setting, based on classical logic, negation (\neg) as the contrariness function and id as the target function, for $S = \{p, q, \neg p \vee \neg q\}$. Then some of the arguments are:

$$\begin{aligned} a &= (\{p\}, p) & d &= (\{p, q\}, \neg(\neg p \vee \neg q)) \\ b &= (\{q\}, q) & e &= (\{p, \neg p \vee \neg q\}, \neg q) \\ c &= (\{\neg p \vee \neg q\}, \neg p \vee \neg q) & f &= (\{q, \neg p \vee \neg q\}, \neg p) \end{aligned}$$

Here, for example, f attacks a, d and e since $p \in \widehat{\text{Supp}(a)} \cap \widehat{\text{Supp}(d)} \cap \widehat{\text{Supp}(e)}$ and $\neg p \in \bar{p}$. Also, d attacks c since $\text{Supp}(c) = \{\neg p \vee \neg q\}$ and $\neg(\neg p \vee \neg q) \in \overline{\neg p \vee \neg q}$. See Figure 1 for a graphical representation of part of the induced argumentation framework.

To determine which arguments can collectively be considered as accepted, Dung-style argumentation semantics [27] can be applied to an argumentation framework.




Figure 1: Graphical representation of part of the argumentation framework from Example 2.

Definition 5 (Argumentation semantics). Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for a setting $\text{AS}_\perp(S)$ and let $S \subseteq \text{Args}_\perp(S)$ be a set of arguments. Then:

- S is *conflict-free* iff there are no $a, b \in S$ such that a attacks b ;
- S *defends* $a \in \text{Args}_\perp(S)$ iff for each attacker $b \in \text{Args}_\perp(S)$ of a there is a $c \in S$ that attacks b ;
- S is *admissible* (Adm) iff it is conflict-free and it defends every $a \in S$; and
- S is *complete* (Cmp) iff it is admissible and it contains every $a \in \text{Args}_\perp(S)$ it defends.

Some specific complete extensions are:

- S is *preferred* (Prf) iff it is \subseteq -maximal complete;
- S is *grounded* (Grd) iff it is \subseteq -minimal complete;
- S is *stable* (Stb) iff it is admissible and for all $a \in \text{Args}_\perp(S) \setminus S$ there is a $b \in S$ that attacks a .

Extensions will be denoted by \mathcal{E} , the set of all Sem-extensions will be denoted by $\text{Sem}(\text{AF}(\text{AS}_\perp(S)))$ for $\text{Sem} \in \{\text{Adm}, \text{Cmp}, \text{Prf}, \text{Grd}, \text{Stb}\}$.¹

In this paper two types of *acceptance relations* are considered. These relations are functions with which sets of accepted formulas can be derived from an argumentation framework, given a semantics.

Definition 6 (Acceptance relations). Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework and let $\text{Sem} \in \{\text{Grd}, \text{Cmp}, \text{Prf}, \text{Stb}\}$. A non-empty set T of \mathcal{L} -formulas is:

- *skeptically accepted* iff for all $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S)))$, $T \subseteq \text{Concs}(\mathcal{E})$;
- *credulously accepted* iff there is some $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S)))$, $T \subseteq \text{Concs}(\mathcal{E})$.

Example 3. In the argumentation framework for $\text{AS}_{\text{CL}}(S)$, with $S = \{p, q, \neg p \vee \neg q\}$ from Example 2, it can be shown that $\text{Args}(\{p, q\})$, $\text{Args}(\{p, \neg p \vee \neg q\})$ and $\text{Args}(\{q, \neg p \vee \neg q\})$ are the extensions for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$.

It follows that a formula ϕ is only skeptically accepted for $\text{Sem} \in \{\text{Grd}, \text{Cmp}\}$ if it is a tautology in classical logic, $p \vee q$ is skeptically accepted for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$, since at least p or q is part of each extension and from either $p \vee q$ can be derived in classical logic and all formulas $\psi \in \{p, q, \neg p \vee \neg q\}$ are credulously accepted for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$.

3.2 Enforcement for Abstract Argumentation

In this section, we recall three types of expansions (adding arguments/attacks) and enforcement as introduced in [8].

Definition 7. (*Expansion*, [8, Definition 5]) An argumentation framework AF^* is an *expansion* of the framework $\text{AF} = \langle \text{Args}, \text{A} \rangle$ iff $\text{AF}^* = \langle \text{Args} \cup \text{Args}^*, \text{A} \cup \text{A}^* \rangle$, such that $\text{Args}^* \neq \emptyset$ and $\text{Args} \cap \text{Args}^* = \emptyset$. Such an expansion is:

- *normal* iff for all a and b , if $(a, b) \in \text{A}^*$ then $a \in \text{Args}^*$ or $b \in \text{Args}^*$;

¹In what follows we will sometimes identify $\text{Grd}(\text{AF}(\text{AS}_\perp(S)))$ with its single element.




Figure 2: Graphical representation of the argumentation framework from Example 4.

- *strong* iff it is normal and for all a and b , if $(a, b) \in A^*$ then it is not the case that $a \in \text{Args}$ and $b \in \text{Args}^*$;
- *weak* iff it is normal and for all a and b if $(a, b) \in A^*$ then it is not the case that $a \in \text{Args}^*$ and $b \in \text{Args}$.

Definition 8. (*Enforcement*, [8, Definition 6]) Let $\text{AF} = \langle \text{Args}, A \rangle$ be an argumentation framework, Sem a semantics and let S be a set of arguments, such that $S \notin \text{Sem}(\text{AF})$. An *enforcement* of S is a framework AF^* such that (1) AF^* is AF or a normal expansion of it and (2) $S \in \text{Sem}(\text{AF}^*)$.

Example 4. Consider the argumentation framework $\text{AF} = \langle \text{Args}, A \rangle$, where $\text{Args} = \{a, b, c\}$ and $A = \{(a, b), (b, a)\}$ shown as the solid part in Figure 2. Now suppose that AF is expanded: $\text{AF}' = \langle \text{Args}', A' \rangle$, where $\text{Args}' = \text{Args} \cup \{d, e\}$ and $A' = A \cup \{(a, d), (b, d), (d, c), (e, d)\}$. The resulting graphical representation is the full graph of Figure 2. AF' is a normal expansion of AF , since no new attacks are added between the arguments of Args . It would be a strong expansion if (a, d) and (b, d) would not be part of A' and it would be a weak expansion if (d, c) would not be part of A' .

4 Enforcement for Structured Argumentation

Enforcement in structured argumentation differs from enforcement for abstract argumentation. While in abstract argumentation enforcement is often based on the addition of arguments or attacks, in structured argumentation it is usually not possible to add one specific argument without adding others as well, viz.

Example 5 (Example 2 continued). Consider again the argumentation setting $\text{AS}_{\text{CL}}(S)$, with $S = \{p, q, \neg p \vee \neg q\}$. If one would want to add the argument $(\{r\}, r)$ to $\text{AF}(\text{AS}_{\text{CL}}(S))$, r has to be added to S : $S' = S \cup \{r\}$. However, then arguments such as $(\{p, r\}, p \wedge r)$ and $(\{r\}, p \vee r)$ are added to $\text{Args}_{\perp}(S')$ as well.

Therefore, the notion of an expansion has to be redefined for a structured setting: rather than changing the argumentation framework directly, the argumentation setting on which the framework is based is expanded.

Definition 9 (Expansion, structured argumentation). Let $\text{AF}(\text{AS}_{\perp}(S))$ be an argumentation framework, for an argumentation setting $\text{AS}_{\perp}(S)$ and some set of formulas $S \subseteq \mathcal{L}$. An *expansion* for $\text{AF}(\text{AS}_{\perp}(S))$ is a set of formulas $S' \subseteq \mathcal{L}$, such that $S' \neq \emptyset$ and $S' \cap S = \emptyset$, and the resulting framework is $\text{AF}(\text{AS}_{\perp}(S \cup S')) = \langle \text{Args}_{\perp}(S \cup S'), A' \rangle$, where $(a, b) \in A'$ iff $a, b \in \text{Args}_{\perp}(S \cup S')$ and a attacks b as defined in Definition 3.

Now enforcement is not about (sets of) arguments, but about (sets of) formulas. Before defining enforcement in terms of sets of formulas, first some useful notions.

Definition 10 ((Strong) (in)consistency). Given an argumentation setting $\text{AS}_{\perp} = \langle \vdash, \bar{\cdot}, \hat{\cdot} \rangle$ a set of formulas S and a set of formulas $\Theta \subseteq S$. Then:

- Θ is *AS_⊥-inconsistent* iff there is a $\gamma \in \Theta$ for which $\Theta \setminus \{\gamma\} \vdash \gamma'$ where $\gamma' \in \bar{\gamma}$. Θ is *strongly AS_⊥(S)-inconsistent* if $\Theta \subseteq \Theta' \subseteq S$ implies that Θ' is inconsistent.
- Θ is *AS_⊥-consistent* iff it is not AS_⊥-inconsistent and Θ is *strongly AS_⊥-consistent* if $\Theta' \subseteq \Theta$ implies that Θ' is AS_⊥-consistent.
- Θ is *maximal AS_⊥-consistent* iff there is no AS_⊥-consistent $\Theta' \subseteq S$ such that $\Theta \subset \Theta'$ and Θ is *maximal strongly AS_⊥(S)-consistent* if $\Theta \subsetneq \Theta' \subseteq S$ implies that Θ' is not strongly AS_⊥(S)-consistent.

We denote $\text{CS}(\text{AS}_-(S))$ [$\text{MCS}(\text{AS}_-(S))$] for all [maximal] strongly $\text{AS}_-(S)$ -consistent sets of S . If the argumentation setting is clear from the context we will write $\text{CS}(S)$ [resp. $\text{MCS}(S)$].

Remark 1. Since \vdash is not assumed to be monotonic, we use the definition of strong inconsistency from [16]. Note that, when \vdash is monotonic, this definition coincides with the definition of (in)consistency from [15].

Example 6 (Example 3 continued). In the argumentation framework from the previous subsection, where $\text{AS}_{\text{CL}} = \langle \vdash_{\text{CL}}, \neg, \text{id} \rangle$ and $S = \{p, q, \neg p \vee \neg q\}$, the set S is AS_{CL} -inconsistent. However, every $S' \subset S$ is AS_{CL} -consistent. In particular, there are three maximally consistent subsets: $\text{MCS}(S) = \{\{p, q\}, \{p, \neg p \vee \neg q\}, \{q, \neg p \vee \neg q\}\}$.

In what follows we will assume that the set of formulas to be enforced is strongly $\text{AS}_-(S)$ -consistent, since otherwise the consistency postulate from [17] could be violated.

Next, we define enforcement for structured argumentation. Enforcing a set of formulas can be done strictly, where the conclusions are exactly that set of formulas, or non-strictly, where the set of formulas has to be part of the conclusions (cf. [8]).

Definition 11 (Enforcement, structured argumentation). Let $\text{AF}(\text{AS}_-(S))$ be an argumentation framework and let $\text{T} \subseteq \mathcal{L}$ be the set of formulas to be enforced. Then:

- T is [strictly] *credulously enforced* by the expansion $S' \subseteq \mathcal{L}$ if there is some extension $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_-(S \cup S')))$ such that $[\text{Concs}(\mathcal{E}) = \text{CN}(\text{T})] \text{Concs}(\mathcal{E}) \supseteq \text{T}$.
- T is [strictly] *skeptically enforced* by the expansion $S' \subseteq \mathcal{L}$ if for all extensions $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_-(S \cup S')))$ it holds that $[\text{Concs}(\mathcal{E}) = \text{CN}(\text{T})] \text{Concs}(\mathcal{E}) \supseteq \text{T}$.

Enforcement of a single formula ϕ means that $\text{T} = \{\phi\}$ in the definition above. The definition is kept general in that $S' \subseteq \mathcal{L}$. Depending on the application S' might be restricted. For example, in the online trade fraud example from Section 2 S' would be restricted to the set of queryables, since these are the only formulas that can be added to the knowledge base.

Example 7 (Example 2 continued). Consider again the framework $\text{AF}(\text{AS}_{\text{CL}}(S))$ for $S = \{p, q, \neg p \vee \neg q\}$. Suppose that $S' = S \cup \{r\}$ as in Example 5. For this expanded set it holds that $\text{Prf}(\text{AF}(\text{AS}_-(S'))) = \{\text{Args}_{\text{CL}}(\{p, q, r\}), \text{Args}_{\text{CL}}(\{p, \neg p \vee \neg q, r\}), \text{Args}_{\text{CL}}(\{q, \neg p \vee \neg q, r\})\}$. Therefore r is both credulously and skeptically enforced by $\{r\}$.

In the next sections formal results on *whether* enforcing a set of formulas is possible are shown. The question of *how* such a set of formulas should be enforced is left for future work. We start by introducing some useful properties.

4.1 Relating Sets of Formulas and Sets of Arguments

Since enforcement is about extensions (sets of arguments) and in the structured setting defined for sets of formulas, sets of formulas and sets of arguments have to be related. In this section results for this relation for static argumentation are presented.²

Most of the results in the remainder of the paper will be shown for argumentation settings with the identity (*id*) target function.³ In such settings, when the set of formulas is AS_- -consistent, there is only one extension and all conclusions of that extension are skeptically accepted.

Lemma 1. *Let $\text{AS}_- = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation setting and let S be a strongly $\text{AS}_-(S)$ -consistent set of \mathcal{L} -formulas. Then: $\text{Sem}(\text{AF}(\text{AS}_-(S))) = \{\text{Args}_-(S)\}$ for $\text{Sem} \in \{\text{Grd}, \text{Cmp}, \text{Prf}, \text{Stb}\}$, and $\text{CN}(S)$ is skeptically accepted in $\text{AF}(\text{AS}_-(S))$.*

The next proposition shows how extensions of argumentation frameworks and sets of formulas are related. While the relation between formal argumentation and reasoning with consistent subsets is well-known [4], our result here (i.e., Proposition 1) is more general than the existing results. This is the case since we employ the general setting from [15], but we restrict the setting less than is done in that paper

²Due to space restrictions we cannot provide proofs in this section. For full proofs we refer to Appendix A.

³See Section 5 for a discussion on this assumption.

(e.g., it is not assumed that the support set of an argument is consistent, nor that \vdash is transitive). Moreover, we apply the more general notion of inconsistency from [16], which is also applicable to nonmonotonic \vdash . It is, however, assumed that the setting is contrapositable (see also Footnote 3):

Definition 12. (*Contrapositable settings [15, Definition 18]*) A setting $(\vdash, \bar{\cdot})$ is *contrapositable* iff for all $\Theta \in \wp_{\text{fin}}(\mathcal{L})$, if $\Theta \vdash \gamma'$ where $\gamma' \in \bar{\gamma}$ then for all $\delta \in \Theta$, $(\Theta \cup \{\gamma\}) \setminus \{\delta\} \vdash \delta'$ for some $\delta' \in \bar{\delta}$. By extension we call $\text{AS}_{\vdash} = \langle \vdash, \bar{\cdot}, \bar{\cdot} \rangle$ contrapositable if $(\vdash, \bar{\cdot})$ is contrapositable.

Proposition 1. *Let $\text{AF}(\text{AS}_{\vdash}(S))$ be such that $\text{AS}_{\vdash}(S) = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable and let $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$:*

1. *if $T \in \text{CS}(S)$, then there is some $T' \supseteq T$ such that $\text{Args}_{\vdash}(T') \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S)))$;*
2. *if $T \in \text{MCS}(S)$, then $\text{Args}_{\vdash}(T) \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S)))$;*
3. *if $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S)))$ then $\text{Supps}(\mathcal{E}) \in \text{CS}(S)$;*
4. *if $\mathcal{E} \in \text{Prf}(\text{AF}(\text{AS}_{\vdash}(S)))$ then $\text{Supps}(\mathcal{E}) \in \text{MCS}(S)$.*

The first item states that for any consistent subset there is a superset from which an extension can be constructed and the second item shows that arguments constructed from a maximally consistent subset form an extension. The third item shows that the union of the support set of all arguments in an extension is always consistent and the fourth shows that the support set of the arguments of a preferred extension is a maximally consistent subset. Since enforcement in structured argumentation is defined for sets of formulas, these results show how sets of formulas that should be enforced and extensions can be related.

4.2 Enforcing Formulas

Throughout this section we will consider several conditions that make enforcement of sets of formulas (im)possible. In addition to general conditions on, for example, the set of formulas that should be enforced and the acceptance relation, we will discuss the expansion types and the notion of monotonicity from [8].

Skeptical enforcement. The type of acceptance (i.e., skeptical or credulous) determines, partially, the possibility of enforcing a set of formulas. Intuitively, it is easier to enforce a set of formulas credulously, since then only one extension has to be considered, while for skeptical enforcement all extensions have to be considered. Indeed, when the set of formulas that should be enforced can only be derived from sets of formulas that are conflicting with the current knowledge base, the set cannot be skeptically enforced. Before we show this, we introduce the next lemma:⁴

Lemma 2. *Let $\text{AS}_{\vdash} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation setting that is contrapositable and let S be a set of \mathcal{L} -formulas. Then: $\text{Grd}(\text{AF}(\text{AS}_{\vdash}(S))) \subseteq \text{Args}_{\vdash}(\text{Free}(S))$.*⁵

Proposition 2. *Let $\text{AS}_{\vdash} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ such that $(\vdash, \bar{\cdot})$ is contrapositable, let S be a set of \mathcal{L} -formulas and suppose that $T \subseteq \mathcal{L}$ has to be skeptically enforced for $\text{Sem} \in \{\text{Grd}, \text{Cmp}\}$. Then T cannot be enforced if there is no minimal strongly $\text{AS}_{\vdash}(S)$ -consistent $S' \subseteq \mathcal{L}$ such that $T \subseteq \text{CN}(S^*)$, where $S^* \subseteq S' \cup S$ and $S' \cup S''$ is strongly $\text{AS}_{\vdash}(S)$ -consistent for each AS_{\vdash} -consistent $S'' \subseteq S$.*

Proof. Let $\text{AS}_{\vdash} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ such that $(\vdash, \bar{\cdot})$ is contrapositable, let $S \subseteq \mathcal{L}$ and suppose that $T \subseteq \mathcal{L}$ has to be skeptically enforced. Moreover, suppose that for each minimal $S' \subseteq \mathcal{L}$ such that there is some minimal $S^* \subseteq S \cup S'$ for which $T \subseteq \text{CN}(S^*)$, there is some AS_{\vdash} -consistent $S'' \subseteq S$ such that $S' \cup S''$ is AS_{\vdash} -inconsistent. It follows that for each S' , there is some $\gamma \in S'$ such that $\gamma \notin \text{Free}(S \cup S')$. By assumption S' is minimal, from which it follows that $\gamma \in S^*$ as well. Since $\text{Grd}(\text{AF}(\text{AS}_{\vdash}(S \cup S'))) \subseteq \text{Args}_{\vdash}(\text{Free}(S \cup S'))$, it follows that $\gamma \notin \text{Supps}(\text{Grd}(\text{AF}(\text{AS}_{\vdash}(S \cup S'))))$. Since S^* is minimal to obtain T , it follows that $T \not\subseteq \text{Concs}(\text{Grd}(\text{AF}(\text{AS}_{\vdash}(S \cup S'))))$. \square

⁴In this section, where space allows we provide proof sketches of (parts of) the proofs. Full proofs can be found in Appendix B.

⁵ $\text{Free}(S)$ is the set of \mathcal{L} -formulas from S that is part of every $T \in \text{MCS}(S)$: $\text{Free}(S) = \bigcap_{T \in \text{MCS}(S)} T$.

The next example illustrates what happens when \mathbb{T} is inconsistent with the current set of formulas S .

Example 8. Consider the setting $\text{AS}_{\text{CL}} = \langle \vdash_{\text{CL}}, \neg, \text{id} \rangle$, let $S = \{p\}$ and suppose that $\mathbb{T} = \{\neg p\}$ has to be enforced. Note that $S \cup \mathbb{T}$ is AS_{CL} -inconsistent. We have that $\text{Grd}(\text{AF}(\text{AS}_{\text{CL}}(S \cup \mathbb{T}))) = \emptyset$ and that $\text{Sem}(\text{AF}(\text{AS}_{\text{CL}}(S \cup \mathbb{T}))) = \{\{\text{Args}_{\text{CL}}(S)\}, \{\text{Args}_{\text{CL}}(\mathbb{T})\}\}$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$. Therefore, while \mathbb{T} is credulously enforced, it is not skeptically enforced.

Consistent sets. Now we consider the relation between extensions and sets of formulas as shown in Proposition 1. In particular, any set of formulas \mathbb{T} can be skeptically [resp. credulously] enforced if there is some set of \mathcal{L} -formulas S' such that \mathbb{T} is part of the consequences of all [resp. some] maximal strongly $\text{AS}_{\vdash}(S)$ -consistent subsets of $S \cup S'$:

Theorem 1. *Let $\text{AF}(\text{AS}_{\vdash}(S))$ be such that $\text{AS}_{\vdash} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable and let $\mathbb{T} \subseteq \mathcal{L}$ be the set that should be enforced. Then:*

1. *If \mathbb{T} can be skeptically enforced then there is some $S' \subseteq \mathcal{L}$ such that $\mathbb{T} \subseteq \text{CN}(S^*)$ and $S^* \subseteq \text{Free}(S \cup S')$ for $\text{Sem} \in \{\text{Grd}, \text{Cmp}\}$;*
2. *\mathbb{T} can be skeptically enforced iff there is some $S' \subseteq \mathcal{L}$ such that for every $S^* \in \text{MCS}(S \cup S')$, $\mathbb{T} \subseteq \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$;*
3. *\mathbb{T} can be strictly skeptically enforced iff there is some $S' \subseteq \mathcal{L}$ such that for every $S^* \in \text{MCS}(S \cup S')$, $\text{CN}(\mathbb{T}) = \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$;*
4. *\mathbb{T} can be credulously enforced iff there is some $S' \subseteq \mathcal{L}$ and some $S^* \in \text{CS}(S \cup S')$ such that $\mathbb{T} \subseteq \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$;*
5. *\mathbb{T} can be strictly credulously enforced iff there is some $S' \subseteq \mathcal{L}$ such that there is some $S^* \in \text{MCS}(S \cup S')$ such that $\text{CN}(\mathbb{T}) = \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$.*

Proof. Let $\text{AF}(\text{AS}_{\vdash}(S))$ be such that $\text{AS}_{\vdash} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable and let $\mathbb{T} \subseteq \mathcal{L}$ be a set of formulas. We show Items 2 and 4:

2. (\Rightarrow) Suppose that \mathbb{T} can be skeptically enforced by expanding S with S' . Then, for each extension $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S \cup S')))$, $\mathbb{T} \subseteq \text{Concs}(\mathcal{E})$. By Proposition 1.2 it follows immediately that for any $S^* \in \text{MCS}(S \cup S')$, $\mathbb{T} \subseteq \text{CN}(S^*)$, since $\text{Args}_{\vdash}(S^*) \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S \cup S')))$ and $\text{Concs}(\mathcal{E}) \subseteq \text{CN}(\text{Args}_{\vdash}(S^*))$.
 (\Leftarrow) Suppose that \mathbb{T} cannot be skeptically enforced, then for each $S' \subseteq \mathcal{L}$ there is some $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S \cup S')))$ such that for some $\phi \in \mathbb{T}$, $\phi \notin \text{Concs}(\mathcal{E})$. By Proposition 1.4 $\text{Supps}(\mathcal{E}) \in \text{MCS}(S \cup S')$. Hence, for any $S' \subseteq \mathcal{L}$, there is some $S^* \in \text{MCS}(S \cup S')$ such that for some $\phi \in \mathbb{T}$, $\phi \notin \text{CN}(S^*)$.
4. (\Rightarrow) Suppose that \mathbb{T} can be credulously enforced. Then there is some $S' \subseteq \mathcal{L}$, such that there is an extension $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S \cup S')))$ for which $\mathbb{T} \subseteq \text{Concs}(\mathcal{E})$. Note that $\mathbb{T} \subseteq \text{CN}(\text{Supps}(\mathcal{E}))$. By Proposition 1.3 it follows that $\text{Supps}(\mathcal{E})$ is consistent.
 (\Leftarrow) Suppose that there is some $S' \subseteq \mathcal{L}$ and some $S^* \in \text{CS}(S \cup S')$ such that $\mathbb{T} \subseteq \text{CN}(S^*)$. By Proposition 1.1 there is some $S^\# \subseteq S^\#$ such that $\text{Args}_{\vdash}(S^\#) \in \text{Sem}(\text{AF}(\text{AS}_{\vdash}(S \cup S')))$. Since $\mathbb{T} \subseteq \text{CN}(S^*)$, for each $\phi \in \mathbb{T}$ there is some $\Gamma \subseteq S^* \subseteq S^\#$ such that $\Gamma \vdash \phi$. Therefore $(\Gamma, \phi) \in \text{Args}_{\vdash}(S^\#)$ and hence $\mathbb{T} \subseteq \text{Concs}(\text{Args}_{\vdash}(S^\#))$. \square

Example 9. (Example 7 continued) With the results from Theorem 1, the skeptical enforcement of r in Example 7 is not surprising: $r \in \bigcap \text{MCS}(\{p, q, \neg p \vee \neg q, r\})$. This also explains why r cannot be strictly enforced: there is no maximally consistent subset of $S \cup \{r\}$ with r as the only member.

Remark 2. In the proof for skeptical enforcement, the results from Items 2 and 4 of Proposition 1 were used, while for credulous enforcement, the results from Items 1 and 3 of Proposition 1 were used. Note that in Proposition 1, Items 1 and 3 are implied by Items 2 and 4 respectively. This means that the results for credulous enforcement are more generally applicable, but also that these results hold when only Items 2 and 4 of Proposition 1 are known for a setting.

Remark 3. In view of this theorem, one might suspect that enforcement in structured argumentation comes down to finding maximally consistent subsets of which the desired set is a consequence. However, some remarks are in order.

- As was shown in [44], it is possible to instantiate abstract argumentation with classical logic and obtain a meaningful setting (i.e., the rationality postulates from [17] are satisfied) of which the conclusions do not correspond to maximally consistent subsets. Therefore, argumentation is a richer formalism than reasoning with maximally consistent subsets and the result from Theorem 1 only illustrates the possibility of enforcement under these conditions. See [4] for a more detailed discussion on and [5] for a characterization of the relation between structured argumentation and maximally consistent subsets.
- In this paper the results are about the (*im*)possibility of enforcement. When it comes to *how* a set of formulas should be enforced the implementation might yield a different result. For example, new information might be obtained over time in a dialogue setting (recall the online trade fraud example from Section 2). In such a case, the result of a question might be different from what was necessary to enforce a set of formulas and with that one answer the possibility of enforcement changes.
- Further possibilities to enforce sets of formulas are discussed in the remainder of the paper. For example, the results from Proposition 3 and Theorem 2 do not rely on the results from Proposition 1 nor is it assumed that the argumentation setup is contrapositable.

Acceptance relation. Next we consider monotonic acceptance relations: when new information is added the acceptance of the previously derived information does not change. While argumentation is mainly employed to model nonmonotonic reasoning, as Lemma 3 shows, not all acceptance relations are non-monotonic. Proposition 3 is therefore relevant in our setting as well.

Definition 13 (Monotonic acceptance relation). Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework. An acceptance relation is called *monotonic* iff for any set of formulas T , if T is accepted in the framework, then T is accepted in any expansion of that framework.

The next proposition shows that a (set of) formula(s) that can be derived from a consistent set of formulas can be enforced in an argumentation framework in which the acceptance relation is monotonic. We give an example of such a relation in Lemma 3.

Proposition 3. *Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ and suppose that the considered acceptance relation is monotonic. Then:*

- Any formula $\phi \in \mathcal{L}$, such that $\Gamma \vdash \phi$ for an AS_\perp -consistent $\Gamma \subseteq \mathcal{L}$, can be enforced by expanding S with Γ ; and
- Let S' be an AS_\perp -consistent set of \mathcal{L} -formulas, such that $T \subseteq \text{CN}(S')$. Then T can be enforced by expanding the framework with S' .

Proof. Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ with a monotonic acceptance relation. We show the first item, the proof of the second item is similar. Suppose that $\Gamma \vdash \phi$ for some strongly AS_\perp -consistent $\Gamma \subseteq \mathcal{L}$ and that ϕ should be enforced. By Lemma 1 it follows that ϕ is accepted in $\text{AF}(\text{AS}_\perp(\Gamma))$. Since acceptance is assumed to be monotonic, ϕ is accepted in $\text{AF}(\text{AS}_\perp(S \cup \Gamma))$. \square

The above results hold for contrapositable frameworks and credulous acceptance:

Lemma 3. *If $\text{AF}(\text{AS}_\perp(S))$ is an argumentation framework for a contrapositable setting $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ then credulous acceptance is monotonic for $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$.*

Proof. Let $\text{AF}(\text{AS}_\perp(S))$ be such that $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable, let $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$ and suppose that T is credulously accepted in $\text{AF}(\text{AS}_\perp(S))$. Moreover, let $S' \subseteq \mathcal{L}$ be arbitrary. Since T is credulously accepted in $\text{AF}(\text{AS}_\perp(S))$, there is some $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S)))$ such that $T \subseteq \text{Concs}(\mathcal{E})$. By Proposition 1.3 $\text{Supps}(\mathcal{E})$ is strongly $\text{AS}_\perp(S)$ -consistent (i.e., $\text{Supps}(\mathcal{E}) \in \text{CS}(S)$) and thus, by Proposition 1.1 there is some $\text{Supps}(\mathcal{E}) \subseteq T' \subseteq S \cup S'$ such that $\text{Args}_\perp(T') \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$. Note that $T \subseteq \text{Concs}(\text{Args}_\perp(T'))$. Therefore T is credulously accepted in $\text{AF}(\text{AS}_\perp(S \cup S'))$, for any S' . \square

The next examples are counterexamples of acceptance relations that are not monotonic. The first shows that skeptical acceptance is non-monotonic.

Example 10. Consider the setting $AS_{CL} = \langle \vdash_{CL}, \neg, id \rangle$ and let $S = \{p\}$. Note that p is a credulous consequence in $AF(AS_{CL}(S))$ and since credulous acceptance is monotonic (Lemma 3) p will remain a credulous consequence. Let $\neg p$ be the formula that should be skeptically enforced. Note that, by Proposition 3, $\neg p$ is credulously enforced by expanding the framework with $S' = \{\neg p\}$. However, then both p and $\neg p$ will be credulously accepted in $AF(AS_{CL}(S \cup S'))$. Therefore, $\neg p$ will never be skeptically accepted.

The second example considers argumentation frameworks in which a preference relation is defined on arguments. Adding a preference relation is a common tool in the argumentation literature to refine conclusions, see e.g., [3, 36]. However, as the example will show, the credulous acceptance relation is no longer monotonic when preferences are added. In this paper we use the following notion of preferences among formulas and sets of formulas:

Definition 14 (Preference relation). Let \mathcal{L} be a formal language, $v : \mathcal{L} \rightarrow \mathbb{N}$ a preference relation on formulas in \mathcal{L} and let $\phi, \psi \in \mathcal{L}$. We denote that ϕ is [strictly] preferred over ψ w.r.t. v by $[\psi \prec_v \phi]$ $\psi \preceq_v \phi$.

The preference relation can be lifted to sets of formulas, such that $S \subseteq \mathcal{L}$ is [strictly] preferred over $T \subseteq \mathcal{L}$ w.r.t. v is denoted by $[T \prec_v S]$ $T \preceq_v S$. The formal definition of the lifting of the preference relation to sets of formulas is left abstract in this paper. Examples can be found in, e.g., [36]. An argument a is preferred over an argument b if $\text{Supp}(a)$ is preferred over $\text{Supp}(b)$, given some preference relation v . We accommodate preferences in the attack relation in the usual way [3, 36]: for $a, b, \in \text{Args}_{\vdash}(S)$, $a \preceq$ -attacks b iff a attacks b and $\text{Supp}(b)$ is not strictly preferred over $\text{Supp}(a)$.

Example 11. Let $AS_{CL} = \langle \vdash_{CL}, \neg, id \rangle$ and $S = \{p\}$ as in the previous example and suppose that there is a preference relation v defined such that $p \prec_v \neg p$. In the flat case, both $\neg p$ and p are credulously accepted in the framework expanded with $\{\neg p\}$, since there was an argument $(\{\neg p\}, \neg p)$ which attacks and is attacked by $(\{p\}, p)$. However, in the prioritized case $(\{p\}, p)$ can no longer attack $(\{\neg p\}, \neg p)$: there is no defense for the \preceq -attack from $(\{\neg p\}, \neg p)$. Hence p is no longer accepted given this v .

Relevance. The results in [15], on non-interference [18], can also be used to say something about the possibility to enforce a (set of) formula(s). Intuitively, non-interference is a helpful property to have, since it indicates that adding irrelevant information does not change the acceptability of the already derived conclusions. In what follows let $\text{Atoms}(S)$ denote the set of atoms that occur in the formulas of S . It is said that two sets of formulas S_1 and S_2 are *syntactically disjoint* (denoted by $S_1 \mid S_2$) if $\text{Atoms}(S_1) \cap \text{Atoms}(S_2) = \emptyset$.

Definition 15. (Non-interference, [18]) An acceptance relation satisfies *non-interference* iff for all $S_1 \cup \{\phi\} \cup S_2 \subseteq \mathcal{L}$ such that $(S_1 \cup \{\phi\}) \mid S_2$ it holds that: ϕ is a consequence of S_1 iff ϕ is a consequence of $S_1 \cup S_2$.

In [15] an extensive discussion can be found on the requirements on the elements of an argumentation setting in order for the acceptability relations to satisfy non-interference (e.g., the deducability relation is assumed to satisfy the basic relevance criterion from relevance logic [6] and the target function is assumed to be monotonic (id is monotonic)). In a dynamic setting, we have the following result:

Theorem 2. Let $AF(AS_{\vdash}(S))$ be such that $AS_{\vdash} = \langle \vdash, \neg, id \rangle$ and that the acceptance relation satisfies non-interference. A set of formulas T can be credulously and skeptically enforced if there is some AS_{\vdash} -consistent $S' \subseteq \mathcal{L}$ such that $T \subseteq \text{CN}(S')$ and $S' \mid S$.

Proof. Let $AF(AS_{\vdash}(S))$ be an argumentation framework such that the considered acceptance relation satisfies non-interference. Moreover, let S' be a strongly AS_{\vdash} -consistent set of \mathcal{L} -formulas, such that $S' \mid S$ and let $T \subseteq \text{CN}(S')$. Since S' is strongly AS_{\vdash} -consistent, it follows by Lemma 1 that T is credulously and skeptically accepted in $AF(AS_{\vdash}(S'))$. Since $S' \mid S$ and the acceptance relation satisfies non-interference, it follows that T is credulously and skeptically accepted in $AF(AS_{\vdash}(S \cup S'))$ as well. \square

Expansion types. Although enforcement in structured argumentation is different from enforcement in abstract argumentation, the expansion types from [8] (recall Definition 7) are available in structured argumentation as well. Intuitively, the next proposition follows since the structure of the existing arguments does not change when an argumentation framework is expanded, hence there are no new attacks between the existing arguments after the expansion.

Proposition 4. *Any expansion of an argumentation framework is normal.*

Proof. Let $\text{AF}(\text{AS}_-(S)) = \langle \text{Args}_-(S), \mathbb{A} \rangle$ be an argumentation framework and suppose that S is expanded by S' . Let the result be $\text{AF}(\text{AS}_-(S \cup S')) = \langle \text{Args}^*, \mathbb{A}^* \rangle$, where $\text{Args}^* = \text{Args}_-(S \cup S')$ and $\mathbb{A}^* = \{(a, b) \in \text{Args}^* \times \text{Args}^* \mid a \text{ attacks } b\}$. Now suppose that S' is such that the expansion is not normal. Then there are $a, b \in \text{Args}_-(S)$ such that $(a, b) \in \mathbb{A}^* \setminus \mathbb{A}$. However, since $a, b \in \text{Args}_-(S)$, by the definition of attack (Definition 3) it follows immediately that a attacks b in $\text{AF}(\text{AS}_-(S))$ as well. A contradiction. \square

The next two remarks discuss conditions on the argumentation setting and framework which ensure that an expansion is not only normal, but also weak or strong.

Remark 4. In some structured argumentation approaches (e.g., ABA [13] and ASPIC⁺ [36]) it is possible to construct arguments that cannot be attacked since these are derived from strict rules and/or premises. On the one hand, if the framework before the expansion consists of such arguments, the expansion is weak: the existing arguments are not attacked. On the other hand, if the new arguments that can be created with the expansion cannot be attacked, the expansion is strong: only the existing arguments can be attacked.

Remark 5. Consider a language \mathcal{L} and a preference relation v for it. If an argumentation framework $\text{AF}(\text{AS}_-(S))$ is expanded in such a way that the new arguments are strictly stronger than the existing ones, the expansion is strong. If the framework is expanded such that the existing arguments are strictly stronger, the expansion is weak.

Monotonicity. In [8] conditions on the semantics and the expansion type are studied to ensure that the expansion is monotonic, i.e., that the number of extensions does not decrease and the acceptance status of the already existing arguments does not change when a framework is expanded. In view of Proposition 1 and Theorem 1 we can show the structured counterpart of [8, Theorem 5].

Proposition 5. *Let $\text{AF}(\text{AS}_-(S))$ be an argumentation framework for a contrapositable $\text{AS}_- = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ and let S' be an expansion. Then, for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$:*

- $|\text{Sem}(\text{AF}(\text{AS}_-(S)))| \leq |\text{Sem}(\text{AF}(\text{AS}_-(S \cup S')))|$;
- $\forall \mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_-(S))), \exists \mathcal{E}' \in \text{Sem}(\text{AF}(\text{AS}_-(S \cup S')))$ such that $\mathcal{E} \subseteq \mathcal{E}'$.

Proof sketch. Let $\text{AF}(\text{AS}_-(S))$ be an argumentation framework for a contrapositable AS_- and let S' be an expansion. Note that MCS is monotonic: for every $T \in \text{MCS}(S)$, there is some $T \subseteq T' \in \text{MCS}(S \cup S')$.

- This follows since $|\text{Stb}(\text{AF}(\text{AS}_-(T)))| \leq |\text{Prf}(\text{AF}(\text{AS}_-(T)))|$ for any set of formulas T (i.e., every stable extension is a preferred extension [27]). Since, $|\text{MCS}(S)| \leq |\text{MCS}(S \cup S')|$, $|\text{Prf}(\text{AF}(\text{AS}_-(S)))| \leq |\text{MCS}(S)|$ (Proposition 1.4) and $|\text{MCS}(S \cup S')| \leq |\text{Stb}(\text{AF}(\text{AS}_-(S \cup S')))|$ (Proposition 1.2).
- Let $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_-(S)))$. Then, by Proposition 1.4 it follows that $\text{Supps}(\mathcal{E}) \in \text{MCS}(S)$. Hence, there is some $T \in \text{MCS}(S \cup S')$ such that $\text{Supps}(\mathcal{E}) \subseteq T$. By Proposition 1.2 it follows that $\text{Args}_-(T) \in \text{Sem}(\text{AF}(\text{AS}_-(S \cup S')))$ (recall that every stable extension is also preferred). Since $\text{Supps}(\mathcal{E}) \subseteq T$, $\mathcal{E} \subseteq \text{Args}_-(T)$. Because \mathcal{E} was arbitrary, this holds for all Prf- and Stb-extensions. \square

Remark 6. [8, Theorem 5] contains a third item (which serves as the converse of the second item) that in a structured setting does not hold without further restrictions. Consider again Example 10, we have that $\text{Prf}(\text{AF}(\text{AS}_{\text{CL}}(\{p\}))) = \{\text{Args}_-(\{p\})\}$, while $\text{Prf}(\text{AF}(\text{AS}_{\text{CL}}(\{p, \neg p\}))) = \{\text{Args}_-(\{p\}), \text{Args}_-(\{\neg p\})\}$. Note that the extension $\text{Args}_-(\{\neg p\})$ does not extend an extension in the framework before the expansion.

5 Discussion

Throughout the paper some assumptions were made to show the results. We will discuss some of these in this section, to illustrate that such restrictions are common in the literature.

In many of the results it was assumed that the target function is *id*. When looking at well-known approaches to structured argumentation [11] and the translation of these approaches as provided by [15] it can be seen that the target function is often *id*. In ABA and ASPIC⁺ this is always the case, because of the translation, and in logic-based argumentation attack rules such as direct defeat and direct undercut are covered by *id*.

The first formal results required that the argumentation setting was contrapositive. In, e.g., [32, 36] the same assumption is made to show, e.g., the rationality postulates from [17] and the relation to reasoning with maximally consistent subsets. As we consider it essential that these rationality postulates are satisfied, the argumentation setting would be contrapositive in most settings anyway.

Like in [15], we do not consider a preference ordering on the arguments. However, throughout the paper some remarks were already made about preference orderings; we plan to formally investigate the use of preferences in future work.

6 Related Work

Enforcement is an important research direction in the study of dynamics in formal argumentation [24]. In [8] (im)possibility results are shown for the enforcement of extensions, based on abstract principles of semantics, rather than specific Dung-style semantics. Moreover, conditions under which the addition of new arguments and attacks between them does not change the acceptance status of already existing arguments are investigated as well. Other, related questions have been investigated such as extension removal [9], enforcement by changing the semantics [23] and the minimal change necessary to enforce an extension [7, 20, 46], all for abstract argumentation frameworks [27].

An enforcement operator for structured argumentation is introduced in [47]. However, the question of enforcement is still at the argument level: how to adjust the knowledge base such that a certain (set of) argument(s) becomes a part of some extension. In our paper we are interested in enforcement on the formula level. This might lead to different conclusion, since, for example, there might be more than one argument for a certain formula.

In a structured argumentation setting we are not aware of any further research on enforcement. There is, however, some work on other aspects of dynamics. In [2], an incremental approach to efficiently recalculating the acceptability status of literals in updated DeLP programs is introduced, in [35] resolutions of attacks are studied in the context of ASPIC⁺, and in [43, 38] the stability of the acceptability status of a certain formula is investigated. Finally, [14] study concepts related to enforcement in (abstract) abductive argumentation frameworks and show that these frameworks can be instantiated by abductive logic programming.

By definition, enforcement is related to belief revision [1, 33]. This relation has been surveyed in, e.g., [30, 29] where it is argued that formal argumentation and belief revision model two complementary aspects of human commonsense reasoning. In particular, where belief revision concerns how an agent's beliefs can be updated consistently, argumentation is concerned with the process of inferring beliefs, and the reasons for and against these beliefs [30, p. 355].

In the dynamic argumentation literature, belief revision (-like) postulates have been employed to handle changes in formal argumentation. We mention some general trends. Many dynamic argumentation approaches that are combined with belief revision postulates are based on a translation of the argumentation framework and notions such as acceptance and Dung-style semantics into logical formulas. For example, [22] introduce a new logical language called YALLA, [25, 26] use the Dynamic Logic of Propositional Assignments and [10] introduce so-called Dung-logics (see [24] for a more detailed overview). Belief revision has also been combined with existing structured argumentation approaches. For example, [42] adjust the belief revision postulates to account for the structure of ASPIC⁺-elements, thus modelling dynamic ASPIC⁺. Furthermore, non-prioritized belief revision is modelled in [41] for a probabilistic variation of DeLP, and revision in logic-based argumentation is modeled in [34]. Each of these examples

studies the question *how* to revise the argumentation framework to obtain good conclusions, which is the central question in belief revision. In contrast, enforcement as studied in this paper is useful for structured argumentation applications based on dialogues, which are exactly the kind of applications that have been implemented at the Dutch National Police and in other application domains, see e.g., [19, 45].

7 Conclusion and Future Work

In this paper we have formulated enforcement for a structured setting: given a set of formulas \mathbb{T} , is it possible to expand the knowledge base such that \mathbb{T} becomes credulously or skeptically accepted? We discussed a real-life application where this question is relevant (Section 2) and argued why enforcement in structured argumentation should be about formulas (Example 5). For the general approach to structured argumentation from [15], we have studied a variety of conditions under which a set of formulas \mathbb{T} can be (strictly) credulously/skeptically enforced: (maximal) consistency of the expansion, relevance, and monotonicity of the acceptance relation. Moreover, we have shown that, although the setting and the notion of enforcement is different from [8], any expansion is normal and satisfies some monotonicity properties. While some of our results build on existing literature, we have shown that the existing studies on static argumentation settings can be employed in dynamic settings as well. This suggests that the extensive research on static structured argumentation can be generalized to dynamic setting, which makes the research better applicable.

As far as we know, this is the first study on enforcement of sets of formulas in a general structured argumentation setting. This opens up the possibility to further investigate dynamics for specific structured settings [11, 13, 36], and to extend the investigation of other notions of dynamics from knowledge representation in formal argumentation.

In addition to extending the current setting with preferences, in future work we will also look into other approaches to structured argumentation that are not covered by the general setting from [15] (e.g., DeLP [31] and claim-augmented argumentation frameworks [28]). Moreover, we will study *how* a set of formulas can be enforced. To this end, we will study different aspects of enforcement for structured argumentation, such as the minimal change necessary to enforce a set of formulas, efficient enforcement, removal of formulas for enforcement, and enforcing the removal of sets of formulas from the conclusion. While some of these more computational aspects of enforcement can be studied in the general setting, for others (e.g., efficient algorithms or complexity studies), we will have to look into specific approaches to structured argumentation.

Acknowledgements

This research has been partly funded by the Dutch Ministry of Justice and the Dutch National Police.

References

- [1] Carlos Alchourrón, Peter Gärdenfors, and David Makinson. On the logic of theory change: Partial meet contraction and revision functions. *Journal of Symbolic Logic*, 50(2):510–530, 1985.
- [2] G. Alfano, S. Greco, F. Parisi, G. I. Simari, and G. R. Simari. An incremental approach to structured argumentation over dynamic knowledge bases. In *Proceedings of KR’18*, pages 78–87, 2018.
- [3] Leila Amgoud and Claudette Cayrol. A reasoning model based on the production of acceptable arguments. *Annals of Mathematics and Artificial Intelligence*, 34(1-3):197–215, 2002.
- [4] O. Arieli, A. Borg, and J. Heyninck. A review of the relations between logical argumentation and reasoning with maximal consistency. *Annals of Mathematics and Artificial Intelligence*, 87(3):187–226, 2019.

- [5] Ofer Arieli, AnneMarie Borg, and Christian Straßer. Characterizations and classifications of argumentative entailments. In *Proceedings of the 18th International Conference on Principles of Knowledge Representation and Reasoning (KR'21)*, 2021. To appear.
- [6] A. Avron. What is relevance logic? *Annals of Pure and Applied Logic*, 165(1):26–48, 2014.
- [7] R. Baumann. What does it take to enforce an argument? Minimal change in abstract argumentation. In *Proceedings of ECAI'12*, pages 127–132. IOS Press, 2012.
- [8] R. Baumann and G. Brewka. Expanding argumentation frameworks: Enforcing and monotonicity results. In *Proceedings of COMMA'10*, pages 75–86. IOS Press, 2010.
- [9] R. Baumann and G. Brewka. Extension removal in abstract argumentation – an axiomatic approach. In *Proceedings of AAI'19*, pages 2670–2677. AAAI press, 2019.
- [10] Ringo Baumann and Gerhard Brewka. AGM meets abstract argumentation: Expansion and revision for Dung frameworks. In Qiang Yang and Michael J. Wooldridge, editors, *Proceedings of the 24th International Conference on Artificial Intelligence (IJCAI'15)*, pages 2734–2740. AAAI Press, 2015.
- [11] P. Besnard, A. García, A. Hunter, S. Modgil, H. Prakken, G. Simari, and F. Toni. Introduction to structured argumentation. *Argument & Computation*, 5(1):1–4, 2014.
- [12] Floris Bex, Bas Testerink, and Joeri Peters. AI for online criminal complaints: From natural dialogues to structured scenarios. In *Workshop proceedings of Artificial Intelligence for Justice at ECAI 2016*, pages 22–29, 2016.
- [13] Andrei Bondarenko, Phan Minh Dung, Robert Kowalski, and Francesca Toni. An abstract, argumentation-theoretic approach to default reasoning. *Artificial Intelligence*, 93(1):63–101, 1997.
- [14] R. Booth, D. Gabbay, S. Kaci, T. Rienstra, and L. van der Torre. Abduction and dialogical proof in argumentation and logic programming. In Torsten Schaub, Gerhard Friedrich, and Barry O'Sullivan, editors, *Proceedings of ECAI'14*, pages 117–122. IOS Press, 2014.
- [15] A. Borg and C. Straßer. Relevance in structured argumentation. In *Proceedings of IJCAI'18*, pages 1753–1759. ijcai.org, 2018. Extended version at: <http://arxiv.org/abs/1809.04861>.
- [16] Gerhard Brewka, Matthias Thimm, and Markus Ulbricht. Strong inconsistency. *Artificial Intelligence*, 267:78–117, 2019.
- [17] M. Caminada and L. Amgoud. On the evaluation of argumentation formalisms. *Artificial Intelligence*, 171(5):286 – 310, 2007.
- [18] M. Caminada, W. Carnielli, and P. Dunne. Semi-stable semantics. *Journal of Logic and Computation*, 22(5):1207–1254, 2011.
- [19] Lisa A. Chalaguine, Emmanuel Hadoux, Fiona Hamilton, Andrew Hayward, Anthony Hunter, Sylwia Polberg, and Henry W. W. Potts. Domain modelling in computational persuasion for behaviour change in healthcare. *CoRR*, abs/1802.10054, 2018.
- [20] S. Coste-Marquis, S. Konieczny, J.-G. Mailly, and P. Marquis. On the revision of argumentation systems: Minimal change of arguments statuses. In *Proceedings of KR'14*, pages 52–61. AAAI Press, 2014.
- [21] Kristijonas Čyras, Tiago Oliveira, Amin Karamlou, and Francesca Toni. Assumption-based argumentation with preferences and goals for patient-centric reasoning with interacting clinical guidelines. *Argument & Computation*, 2020.
- [22] Florence Dupin de Saint-Cyr, Pierre Bisquert, Claudette Cayrol, and Marie-Christine Lagasquie-Schiex. Argumentation update in YALLA (yet another logic language for argumentation). *International Journal of Approximate Reasoning*, 75:57–92, 2016.

- [23] S. Doutre and J.-G. Mailly. Semantic change and extension enforcement in abstract argumentation. In *Proceedings of SUM'17*, pages 194–207. Springer, 2017.
- [24] S. Doutre and J.-G. Mailly. Constraints and changes: A survey of abstract argumentation dynamics. *Argument & Computation*, 9(3):223–248, 2018.
- [25] Sylvie Doutre, Andreas Herzig, and Laurent Perrussel. A dynamic logic framework for abstract argumentation. In Chitta Baral, Giuseppe De Giacomo, and Thomas Eiter, editors, *Proceedings of the 14th International Conference on Principles of Knowledge Representation and Reasoning (KR'14)*, pages 62–71. AAAI Press, 2014.
- [26] Sylvie Doutre, Faustine Maffre, and Peter McBurney. A dynamic logic framework for abstract argumentation: Adding and removing arguments. In Salem Benferhat, Karim Tabia, and Moonis Ali, editors, *Proceedings of the 30th International Conference on Industrial, Engineering, Other Applications of Applied Intelligent Systems (IEA/AIE'17)*, volume 10351 of *Lecture Notes in Computer Science*, pages 295–305. Springer, 2017.
- [27] P. M. Dung. On the acceptability of arguments and its fundamental role in nonmonotonic reasoning, logic programming and n-person games. *Artificial Intelligence*, 77(2):321–357, 1995.
- [28] Wolfgang Dvořák and Stefan Woltran. Complexity of abstract argumentation under a claim-centric view. *Artificial Intelligence*, 285:103290, 2020.
- [29] Marcelo Falappa, Alejandro García, Gabriele Kern-Isberner, and Guillermo Simari. On the evolving relation between belief revision and argumentation. *The Knowledge Engineering Review*, 26(1):35–43, 2011.
- [30] Marcelo Alejandro Falappa, Gabriele Kern-Isberner, and Guillermo Ricardo Simari. *Belief Revision and Argumentation Theory*, pages 341–360. Springer, 2009.
- [31] Alejandro García and Guillermo Simari. Defeasible logic programming: an argumentative approach. *Theory and Practice of Logic Programming*, 4(1&2):95–138, 2004.
- [32] Jesse Heyninck and Ofer Arieli. On the semantics of simple contrapositive assumption-based argumentation frameworks. In Sanjay Modgil, Katarzyna Budzyska, and John Lawrence, editors, *Proceedings of the 7th International Conference on Computation Models of Argument (COMMA'18)*, *Frontiers in Artificial Intelligence and Applications* 305, pages 9–20. IOS Press, 2018.
- [33] Hirofumi Katsuno and Alberto Mendelzon. On the difference between updating a knowledge base and revising it. In James F. Allen, Richard Fikes, and Erik Sandewall, editors, *Proceedings of the 2nd International Conference on Principles of Knowledge Representation and Reasoning (KR'91)*, pages 387–394. Morgan Kaufmann, 1991.
- [34] P. Krümpelmann, M. Thimm, M. Falappa, A. García, G. Kern-Isberner, and G. R. Simari. Selective revision by deductive argumentation. In *Proceedings of TAFE'11*, pages 147–162. Springer, 2012.
- [35] S. Modgil and H. Prakken. Resolutions in structured argumentation. In *Proceedings of COMMA'12*, pages 310–321. IOS Press, 2012.
- [36] S. Modgil and H. Prakken. A general account of argumentation with preferences. *Artificial Intelligence*, 195:361–397, 2013.
- [37] Daphne Odekerken and Floris Bex. Towards transparent human-in-the-loop classification of fraudulent web shops. In Serena Villata, Jakub Harašta, and Petr Křemen, editors, *Proceedings of the 33rd Conference on Legal Knowledge and Information Systems (JURIX'20)*, volume 334 of *Frontiers in Artificial Intelligence and Applications*, pages 239–242. IOS Press, 2020.

- [38] Daphne Odekerken, AnneMarie Borg, and Floris Bex. Estimating stability for efficient argument-based inquiry. In Henry Prakken, Stefano Bistarelli, Francesco Santini, and Carlo Taticchi, editors, *Proceedings of the 8th International Conference on Computational Models of Argument (COMMA'20)*, volume 326 of *Frontiers in Artificial Intelligence and Applications*, pages 307–318. IOS Press, 2020.
- [39] Henry Prakken. An abstract framework for argumentation with structured arguments. *Argument & Computation*, 1(2):93–124, 2010.
- [40] Henry Prakken. An Argumentation-Based Analysis of the Simonshaven Case. *Topics in Cognitive Science - Special Issue on Rational Models of Legal Proof*, 12(4):1068–1091, 2020.
- [41] Paulo Shakarian, Gerardo Simari, Geoffrey Moores, Damon Paulo, Simon Parsons, Marcelo A. Falappa, and Ashkan Aleali. Belief revision in structured probabilistic argumentation. *Annals of Mathematics and Artificial Intelligence*, 78(3):259–301, 2016.
- [42] M. Snaith and C. Reed. Argument Revision. *Journal of Logic and Computation*, 27(7):2089–2134, 2016.
- [43] B. Testerink, D. Odekerken, and F. Bex. A method for efficient argument-based inquiry. In *Proceedings of FQAS'19*, pages 114–125. Springer, 2019.
- [44] Srdjan Vesic and Leendert W. N. van der Torre. Beyond maxi-consistent argumentation operators. In Luis Fariñas del Cerro, Andreas Herzig, and Jérôme Mengin, editors, *Proceedings of the 13th Conference on Logics in Artificial Intelligence, (JELIA'12)*, volume 7519 of *Lecture Notes in Computer Science*, pages 424–436. Springer, 2012.
- [45] Jacky Visser, John Lawrence, and Chris Reed. Reason-checking fake news. *Communications of the ACM*, 63(11):38–40, 2020.
- [46] J. Wallner, A. Niskanen, and M. Järvisalo. Complexity results and algorithms for extension enforcement in abstract argumentation. *Journal of Artificial Intelligence Research*, 60:1–40, 2017.
- [47] Johannes Wallner. Structural constraints for dynamic operators in abstract argumentation. *Argument & Computation*, 11(1–2):151–190, 2020.
- [48] Zhiwei Zeng, Zhiqi Shen, Benny Toh Hsiang Tan, Jing Jih Chin, Cyril Leung, Yu Wang, Ying Chi, and Chunyan Miao. Explainable and Argumentation-based Decision Making with Qualitative Preferences for Diagnostics and Prognostics of Alzheimer’s Disease. In *Proceedings of the 17th International Conference on Principles of Knowledge Representation and Reasoning*, pages 816–826, 9 2020.

A Proofs Relating Sets of Formulas and Sets of Arguments

We start the appendix by providing full proofs of the results from Section 4.1.

Lemma 1. *Let $AS_{\perp} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation setting and let S be a strongly AS_{\perp} -consistent set of \mathcal{L} -formulas. Then: $\text{Sem}(AF(AS_{\perp}(S))) = \{Args_{\perp}(S)\}$ for $\text{Sem} \in \{\text{Grd}, \text{Cmp}, \text{Prf}, \text{Stb}\}$, and $\text{CN}(S)$ is skeptically accepted in $AF(AS_{\perp}(S))$.*

Proof. Let $AS_{\perp} = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation setting and let S be a strongly AS_{\perp} -consistent set of \mathcal{L} -formulas. We show that $Args_{\perp}(S)$ is not attacked and is therefore the single extension for $\text{Sem} \in \{\text{Grd}, \text{Cmp}, \text{Prf}, \text{Stb}\}$. Suppose towards a contradiction, that there are $a, b \in Args_{\perp}(S)$ such that $a = (\Gamma, \phi)$, $b = (\Delta, \psi)$ and $(a, b) \in A$. Thus there is some $\delta \in \Delta$ such that $\phi \in \bar{\delta}$. By Definition 10, $\Gamma \cup \{\delta\}$ is AS_{\perp} -inconsistent. A contradiction, since $\Gamma \cup \delta \subseteq S$ is strongly AS_{\perp} -consistent. Hence no argument in

$\text{Args}_-(S)$ is attacked. By the definition of $\text{Args}_-(S)$:

$$\begin{aligned}\text{Concs}(\text{Args}_-(S)) &= \{\text{Conc}(a) \mid a \in \text{Args}_-(S)\} \\ &= \{\phi \mid (\Gamma, \phi) \in \text{Args}_-(S)\} \\ &= \{\phi \mid \Gamma \vdash \phi \text{ for some } \Gamma \subseteq S\} \\ &= \{\phi \mid \exists \Gamma \subseteq S \text{ s.t. } \Gamma \vdash \phi\} = \text{CN}(S).\end{aligned}$$

It follows that $\text{CN}(S)$ is skeptically accepted. \square

When the target function is id the argumentation framework satisfies support closure: given an extension, any argument that can be constructed from formulas already used in the support set of arguments in that extension will be part of that extension. This result will be used in the proof of Proposition 1.

Lemma 4. $AF(\mathcal{AS}_-(S))$ for $\mathcal{AS}_- = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ satisfies support closure: if $\text{Supp}(a) \subseteq \text{Supps}(\mathcal{E})$ then $a \in \mathcal{E}$, for $\text{Sem} \in \{\text{Grd}, \text{Cmp}, \text{Prf}, \text{Stb}\}$.

Proof. Let $AF(\mathcal{AS}_-(S))$ be such that $\mathcal{AS}_- = \langle \vdash, \bar{\cdot}, \text{id} \rangle$, let $\mathcal{E} \in \text{Sem}(AF(\mathcal{AS}_-(S)))$ for $\text{Sem} \in \{\text{Grd}, \text{Cmp}, \text{Prf}, \text{Stb}\}$ and let $a \in \text{Args}_-(S)$ such that $\text{Supp}(a) \subseteq \text{Supps}(\mathcal{E})$. If a is not attacked, by the completeness of \mathcal{E} it follows that $a \in \mathcal{E}$. Now suppose that there is some $b \in \text{Args}_-(S)$ such that b attacks a . Then there is some $\gamma \in \widehat{\text{Supp}(a)} = \text{Supp}(a)$ such that $\text{Conc}(b) \in \bar{\gamma}$. By assumption, there is some $c \in \mathcal{E}$ such that $\gamma \in \text{Supp}(c)$ as well. Hence b attacks c . Since $c \in \mathcal{E}$, there is some $d \in \mathcal{E}$ such that d defends c against the attack from b and therefore defends a against the attack from b as well. Again by the completeness of \mathcal{E} , $a \in \mathcal{E}$. \square

In addition to the above lemma, we will also use the following remark, sometimes implicitly.

Remark 7. Let $\mathcal{AS}_- = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation setting, S a set of \mathcal{L} -formulas and let $S' \in \text{CS}(S)$. Then there is some $T \in \text{MCS}(S)$ such that $S' \subseteq T$.

Proposition 1. Let $AF(\mathcal{AS}_-(S))$ be such that $\mathcal{AS}_-(S) = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable and let $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$:

1. if $T \in \text{CS}(S)$, then there is some $T' \supseteq T$ such that $\text{Args}_-(T') \in \text{Sem}(AF(\mathcal{AS}_-(S)))$;
2. if $T \in \text{MCS}(S)$, then $\text{Args}_-(T) \in \text{Sem}(AF(\mathcal{AS}_-(S)))$;
3. if $\mathcal{E} \in \text{Sem}(AF(\mathcal{AS}_-(S)))$ then $\text{Supps}(\mathcal{E}) \in \text{CS}(S)$;
4. if $\mathcal{E} \in \text{Prf}(AF(\mathcal{AS}_-(S)))$ then $\text{Supps}(\mathcal{E}) \in \text{MCS}(S)$.

Proof. Let $AF(\mathcal{AS}_-(S))$ be such that $\mathcal{AS}_-(S) = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable and let $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$.

1. Let $T' \in \text{CS}(S)$. Then, by Remark 7, there is some $T \subseteq T'$ such that $T \in \text{MCS}(S)$. By Lemma 1 it follows that $\text{Args}_-(T)$ is conflict-free. It can be shown that $\text{Args}_-(T)$ is stable (and therefore preferred and complete as well).

Suppose that there is some $b = (\Delta, \delta) \in \text{Args}_-(S) \setminus \text{Args}_-(T)$. Then there is some $\phi \in \Delta \setminus T$. By assumption, T is maximal strongly $\mathcal{AS}_-(S)$ -consistent. Therefore $T \cup \{\phi\}$ is not strongly $\mathcal{AS}_-(S)$ -consistent. From which it follows that there is some $\Gamma \subseteq T \cup \{\phi\}$ and some $\gamma \in \Gamma$ such that $\Gamma \setminus \{\gamma\} \vdash \gamma'$ for some $\gamma' \in \bar{\gamma}$. If $\gamma = \phi$, then $\gamma' \in \bar{\phi}$ and $a = (\Gamma \setminus \{\phi\}, \gamma') \in \text{Args}_-(T)$. If $\gamma \neq \phi$, then $\phi \in \Gamma \setminus \{\gamma\}$ (since $\Gamma \setminus \{\phi\} \subseteq T$), by contraposition $\Gamma \setminus \{\phi\} \vdash \phi'$ for $\phi' \in \bar{\phi}$. Then also $a = (\Gamma \setminus \{\phi\}, \phi') \in \text{Args}_-(T)$. In both cases a attacks b . It follows that $\text{Args}_-(T) \in \text{Stb}(AF(\mathcal{AS}_-(S)))$. Since any stable extension is also preferred and complete $\text{Args}_-(T) \in \text{Sem}(AF(\mathcal{AS}_-(S)))$ for $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$.

2. This follows immediately by the proof of Item 1.
3. Now suppose that $\mathcal{E} \in \text{Sem}(AF(\mathcal{AS}_-(S)))$. Let $T = \text{Supps}(\mathcal{E})$ and suppose that $T \notin \text{CS}(S)$. Then there is some $\Gamma \subseteq T$ and some $\gamma \in \Gamma$ such that $\Gamma \setminus \{\gamma\} \vdash \gamma'$ where $\gamma' \in \bar{\gamma}$. By Lemma 4, $b = (\Gamma \setminus \{\gamma\}, \gamma') \in \mathcal{E}$. However, since $\gamma \in T$, there is some $a \in \mathcal{E}$ such that $\gamma \in \text{Supp}(a)$. Hence b attacks a . A contradiction to the conflict-freeness of \mathcal{E} . Thus T is strongly $\mathcal{AS}_-(S)$ -consistent.

4. Let $\mathcal{E} \in \text{Prf}(\text{AF}(\text{AS}_\perp(S)))$. By Item 3 $\text{Supps}(\mathcal{E})$ is strongly AS_\perp -consistent. Suppose that $\text{Supps}(\mathcal{E})$ is not maximal strongly $\text{AS}_\perp(S)$ -consistent. Then, by Remark 7, there is some $S \supseteq T \supset \text{Supps}(\mathcal{E})$ such that T is maximal strongly $\text{AS}_\perp(S)$ -consistent. By Item 2, $\text{Args}_\perp(T) \in \text{Prf}(\text{AF}(\text{AS}_\perp(S)))$. However, $\mathcal{E} \not\subseteq \text{Args}_\perp(T)$. A contradiction. Hence $\text{Supps}(\mathcal{E}) = T$. \square

B Proofs Enforcing Formulas

In this appendix full proofs of the results from Section 4.2 are collected.

While $\text{Free}(S)$ is not necessarily strongly consistent [16], from Proposition 1 it is known that the support set of the grounded extension is strongly consistent.

Lemma 2. *Let $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation setting that is contrapositable and let S be a set of \mathcal{L} -formulas. Then: $\text{Grd}(\text{AF}(\text{AS}_\perp(S))) \subseteq \text{Args}_\perp(\text{Free}(S))$.⁶*

Proof. Let $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ be an argumentation system that is contrapositable and let S be a set of \mathcal{L} -formulas. Moreover, let $\mathcal{E}_{\text{grd}} \in \text{Grd}(\text{AF}(\text{AS}_\perp(S)))$ be the grounded extension and $a \in \mathcal{E}_{\text{grd}}$. Suppose, towards a contradiction, that there is some $\gamma \in \text{Supp}(a)$ such that $\gamma \notin \text{Free}(S)$. Then there is some $T \in \text{MCS}(S)$ such that $\gamma \notin T$. By Proposition 1.2, $\text{Args}_\perp(T) \in \text{Stb}(\text{AF}(\text{AS}_\perp(S)))$. Since $\gamma \notin T$, $a \notin \text{Args}_\perp(T)$. However, since every stable extension is complete, $a \notin \mathcal{E}_{\text{grd}}$. A contradiction. \square

Theorem 1. *Let $\text{AF}(\text{AS}_\perp(S))$ be such that $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ is contrapositable and let $T \subseteq \mathcal{L}$ be the set that should be enforced. Then:*

1. *If T can be skeptically enforced then there is some $S' \subseteq \mathcal{L}$ such that $T \subseteq \text{CN}(S^*)$ and $S^* \subseteq \text{Free}(S \cup S')$ for $\text{Sem} \in \{\text{Grd}, \text{Cmp}\}$;*
2. *T can be skeptically enforced iff there is some $S' \subseteq \mathcal{L}$ such that for every $S^* \in \text{MCS}(S \cup S')$, $T \subseteq \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$;*
3. *T can be strictly skeptically enforced iff there is some $S' \subseteq \mathcal{L}$ such that for every $S^* \in \text{MCS}(S \cup S')$, $\text{CN}(T) = \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$;*
4. *T can be credulously enforced iff there is some $S' \subseteq \mathcal{L}$ and some $S^* \in \text{CS}(S \cup S')$ such that $T \subseteq \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Cmp}, \text{Prf}, \text{Stb}\}$;*
5. *T can be strictly credulously enforced iff there is some $S' \subseteq \mathcal{L}$ such that there is some $S^* \in \text{MCS}(S \cup S')$ such that $\text{CN}(T) = \text{CN}(S^*)$ for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$.*

Proof. Let $\text{AF}(\text{AS}_\perp(S))$ be such that $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ and let $T \subseteq \mathcal{L}$ be a set of formulas. Consider each item, in both directions:

1. This follows immediately from Proposition 2.
2. (\Rightarrow) Suppose that T can be skeptically enforced by expanding S with S' . Then, for each extension $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$, $T \subseteq \text{Concs}(\mathcal{E})$. By Proposition 1.2 it follows immediately that for any $S^* \in \text{MCS}(S \cup S')$, $T \subseteq \text{CN}(S^*)$, since $\text{Args}_\perp(S^*) \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$ and $\text{Concs}(\mathcal{E}) \subseteq \text{CN}(\text{Args}_\perp(S^*))$.
 (\Leftarrow) Suppose that T cannot be skeptically enforced, then for each $S' \subseteq \mathcal{L}$ there is some $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$ such that for some $\phi \in T$, $\phi \notin \text{Concs}(\mathcal{E})$. By Proposition 1.4 $\text{Supps}(\mathcal{E}) \in \text{MCS}(S \cup S')$. Hence, for any $S' \subseteq \mathcal{L}$, there is some $S^* \in \text{MCS}(S \cup S')$ such that for some $\phi \in T$, $\phi \notin \text{CN}(S^*)$.

⁶ $\text{Free}(S)$ is the set of \mathcal{L} -formulas from S that is part of every $T \in \text{MCS}(S)$: $\text{Free}(S) = \bigcap_{T \in \text{MCS}(S)} T$.

3. (\Rightarrow) Suppose that \mathbb{T} can be strictly skeptically enforced by expanding the framework with S' . Then for any extension $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$, $\text{CN}(\mathbb{T}) = \text{Concs}(\mathcal{E})$. Like for Item 2, by Proposition 1.2 it follows that for all $S^* \in \text{MCS}(S \cup S')$, $\text{CN}(\mathbb{T}) = \text{CN}(S^*)$.
- (\Leftarrow) Now assume that \mathbb{T} cannot be strictly skeptically enforced. If \mathbb{T} cannot be skeptically enforced either, it follows by the previous item that for each $S' \subseteq \mathcal{L}$, there is some $S^* \in \text{MCS}(S \cup S')$ such that for some $\phi \in \mathbb{T}$, $\phi \notin \text{CN}(S^*)$. If \mathbb{T} can be skeptically enforced, then for each $S' \subseteq \mathcal{L}$ such that there is some $S^* \in \text{MCS}(S \cup S^*)$ with $\mathbb{T} \subseteq \text{CN}(S^*)$ (note that also $\text{CN}(\mathbb{T}) \subseteq \text{CN}(S^*)$), there is some $\phi \in \text{CN}(S^*) \setminus \text{CN}(\mathbb{T})$. Hence $\text{CN}(\mathbb{T}) \neq \text{CN}(S^*)$ for any $S' \subseteq \mathcal{L}$ and any $S^* \in \text{MCS}(S \cup S')$.
4. (\Rightarrow) Suppose that \mathbb{T} can be credulously enforced. Then there is some $S' \subseteq \mathcal{L}$, such that there is an extension $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$ for which $\mathbb{T} \subseteq \text{Concs}(\mathcal{E})$. Note that $\mathbb{T} \subseteq \text{CN}(\text{Supps}(\mathcal{E}))$. By Proposition 1.3 it follows that $\text{Supps}(\mathcal{E})$ is consistent.
- (\Leftarrow) Suppose that there is some $S' \subseteq \mathcal{L}$ and some $S^* \in \text{CS}(S \cup S')$ such that $\mathbb{T} \subseteq \text{CN}(S^*)$. By Proposition 1.1 there is some $S^* \subseteq S^\#$ such that $\text{Args}_\perp(S^\#) \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$. Since $\mathbb{T} \subseteq \text{CN}(S^*)$, for each $\phi \in \mathbb{T}$ there is some $\Gamma \subseteq S^* \subseteq S^\#$ such that $\Gamma \vdash \phi$. Therefore $(\Gamma, \phi) \in \text{Args}_\perp(S^\#)$ and hence $\mathbb{T} \subseteq \text{Concs}(\text{Args}_\perp(S^\#))$.
5. (\Rightarrow) Assume that \mathbb{T} can be strictly credulously enforced by some $S' \subseteq \mathcal{L}$. Then there is some $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$ such that $\text{Concs}(\mathcal{E}) = \text{CN}(\mathbb{T})$. By Proposition 1.4 it follows that $\text{Supps}(\mathcal{E}) \in \text{MCS}(S \cup S')$. Since $\text{CN}(\text{Supps}(\mathcal{E})) = \text{Concs}(\mathcal{E}) = \text{CN}(\mathbb{T})$, it follows that there is some $S^* \in \text{MCS}(S \cup S')$ such that $\text{CN}(\mathbb{T}) = \text{CN}(S^*)$.
- (\Leftarrow) Now assume that there is some $S' \subseteq \mathcal{L}$ and some $S^* \in \text{MCS}(S \cup S')$ such that $\text{CN}(\mathbb{T}) = \text{CN}(S^*)$. By Proposition 1.2, $\text{Args}_\perp(S^*) \in \text{Stb}(\text{AF}(\text{AS}_\perp(S \cup S')))$. Since $\text{Concs}(\text{Args}_\perp(S^*)) = \text{CN}(S^*) = \text{CN}(\mathbb{T})$ it follows that \mathbb{T} can be strictly credulously enforced by expanding the framework with S' . \square

Proposition 3. *Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ and suppose that the considered acceptance relation is monotonic. Then:*

- Any formula $\phi \in \mathcal{L}$, such that $\Gamma \vdash \phi$ for an AS_\perp -consistent $\Gamma \subseteq \mathcal{L}$, can be enforced by expanding S with Γ ; and
- Let S' be an AS_\perp -consistent set of \mathcal{L} -formulas, such that $\mathbb{T} \subseteq \text{CN}(S')$. Then \mathbb{T} can be enforced by expanding the framework with S' .

Proof. Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ with a monotonic acceptance relation. Consider both items:

- Suppose that $\Gamma \vdash \phi$ for some strongly AS_\perp -consistent $\Gamma \subseteq \mathcal{L}$ and that ϕ should be enforced. By Lemma 1 it follows that ϕ is accepted in $\text{AF}(\text{AS}_\perp(\Gamma))$. Since acceptance is assumed to be monotonic, ϕ is accepted in $\text{AF}(\text{AS}_\perp(S \cup \Gamma))$ as well.
- Let S' be a strongly AS_\perp -consistent set of \mathcal{L} formulas such that $\mathbb{T} \subseteq \text{CN}(S')$ and suppose that \mathbb{T} has to be enforced. Since S' is strongly $\text{AS}_\perp(S)$ -consistent, by Lemma 1 $\text{CN}(S')$ is accepted in $\text{AF}(\text{AS}_\perp(S'))$. Since acceptance is assumed to be monotonic it follows that \mathbb{T} is accepted in $\text{AF}(\text{AS}_\perp(S \cup S'))$. Hence \mathbb{T} is enforced by the expansion of S' . \square

Proposition 5. *Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for a contrapositable $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ and let S' be an expansion. Then, for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$:*

- $|\text{Sem}(\text{AF}(\text{AS}_\perp(S)))| \leq |\text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))|$;
- $\forall \mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_\perp(S))), \exists \mathcal{E}' \in \text{Sem}(\text{AF}(\text{AS}_\perp(S \cup S')))$ such that $\mathcal{E} \subseteq \mathcal{E}'$.

Proof. Let $\text{AF}(\text{AS}_\perp(S))$ be an argumentation framework for $\text{AS}_\perp = \langle \vdash, \bar{\cdot}, \text{id} \rangle$ and let S' be an expansions. Consider each of the items:

- Note that, given the definition of strong consistency (Definition 10), $|\text{MCS}(S)| \leq |\text{MCS}(S \cup S')|$. By Proposition 1.4 it is known that $|\text{Prf}(\text{AF}(\text{AS}_+(S)))| \leq |\text{MCS}(S)|$. By Proposition 1.2 it is known that $|\text{MCS}(S \cup S')| \leq |\text{Stb}(\text{AF}(\text{AS}_+(S \cup S')))|$. Since any stable extension is also a preferred extension [27] and therefore $|\text{Stb}(\text{AF}(\text{AS}_+(T)))| \leq |\text{Prf}(\text{AF}(\text{AS}_+(T)))|$ for any set of formulas T , it follows that $|\text{Stb}(\text{AF}(\text{AS}_+(S)))| \leq |\text{MCS}(S)|$ and $|\text{MCS}(S \cup S')| \leq |\text{Prf}(\text{AF}(\text{AS}_+(S \cup S')))|$ as well. It therefore follows that $|\text{Sem}(\text{AF}(\text{AS}_+(S)))| \leq |\text{Sem}(\text{AF}(\text{AS}_+(S \cup S')))|$, for $\text{Sem} \in \{\text{Prf}, \text{Stb}\}$.
- Let $\mathcal{E} \in \text{Sem}(\text{AF}(\text{AS}_+(S)))$. Then, by Proposition 1.4 it follows that $\text{Supps}(\mathcal{E}) \in \text{MCS}(S)$. Hence, there is some $T \in \text{MCS}(S \cup S')$ such that $\text{Supps}(\mathcal{E}) \subseteq T$. By Proposition 1.2 it follows that $\text{Args}_+(\mathcal{E}) \in \text{Sem}(\text{AF}(\text{AS}_+(S \cup S')))$ (recall that every stable extension is also preferred). Since $\text{Supps}(\mathcal{E}) \subseteq T$, $\mathcal{E} \subseteq \text{Args}_+(T)$. Because \mathcal{E} was arbitrary, this holds for all Prf- and Stb-extensions. \square